

# brick light

**LED**

powered by  
Citizen CLL130  
Transformer included



simmetrico  
symmetric  
symétriques  
simétrico  
symmetrisch

example code:

art.	LED	colour
410	L6	ngg

art.	electrification	colour
410	E27	ngg

art.  
410  
411  
412  
413

design Ufficio Tecnico Landa




RECESSED

24

corpo alluminio pressofuso  
body in die casting aluminium  
corps en aluminium moulé  
sous pression  
cuerpo aluminio inyectado  
Körper aus Aluminium-  
Druckguss

diffusore vetro opale  
diffuser glass opal  
diffuseur verre opaque  
difusor vidrio ópalo  
Diffuser Glas opal






410




411

frontale in alluminio  
/ aluminium frame /  
cadre en aluminium  
cornis aluminio  
/ Rahmen aus  
Aluminium



BOX DIMENSION



FOR TECHNICAL DETAILS VISIT  
[www.landa.it](http://www.landa.it)

IP65

art.	art.		W	V	Type	Ra
410L6N	411L6N	○	6	240	4000K 660LM	80
410L6H	411L6H	●	6	240	3000K 600LM	80
410	411		1x40		E27	




ELECTRIFICATION

**LED & INSTALLATION**

dettagli / details / details  
detalles / details:  
p.A52 - A53

Energy efficiency classes



code ....L6

A++ ÷ A

max 40 W



4,5

max 20 W

4,5



E27

max 15 W

6



A+ ÷ E

## brick light

Projectors

NEW  
Recessed

Contemporary


Traditional



RECESSED  
25






412




413

frontale in acciaio  
inox AISI 316L /  
stainless steel AISI  
316L frame / cadre  
en acier inoxydable  
AISI 316L / cornis  
acero inox AISI 316L  
/ Rahmen aus  
Edelstahl AISI 316L



BOX DIMENSION



art.	art.		W	V	Type	Light bulb icon	Ra
412L6N	413L6N	○	6	240	4000K 660LM		80
412L6H	413L6H	●			3000K 600LM		80
412	413		1x40		E27	Light bulb icon	



# brick light

**LED**

powered by  
Citizen CLL130  
Transformer included

simmetrico  
symmetric  
symétriques  
simétrico  
symmetrisch

example code:

art.	LED			colour
410	L6	H	M	ngg
art.	electrification			colour
410	E27		M	ngg

art.  
410...M  
411...M  
412...M  
413...M

design Ufficio Tecnico Landa



RECESSED

26

corpo alluminio pressofuso  
body in die casting aluminium  
corps en aluminium moulé  
sous pression  
cuerpo aluminio inyectado  
Körper aus Aluminium-  
Druckguss

diffusore vetro opale  
diffuser glass opal  
diffuseur verre opaque  
difusor vidrio ópalo  
Diffuser Glas opal






410...M


frontale in alluminio  
/ aluminium frame /  
cadre en aluminium  
cornis aluminium  
/ Rahmen aus  
Aluminium



411...M



code: ...M



230x88 mm

FOR TECHNICAL DETAILS VISIT  
[www.landa.it](http://www.landa.it)

IP65

art.	art.		W	V	Type	Ra
410L6NM	411L6NM	○	6	240	4000K 660LM	80
410L6HM	411L6HM	●			3000K 600LM	80
410M	411M		1x40		E27	




ELECTRIFICATION




**LED & INSTALLATION**

dettagli / details / details  
detalles / details:  
p.A52 - A53

Energy efficiency classes



code ...L6  
A++ ÷ A



A+ ÷ E



## brick light

Projectors

NEW  
Recessed

Contemporary

Traditional



ENERGY  
SAVING

RECESSED  
27






412...M




413...M

frontale in acciaio  
inox AISI 316L /  
stainless steel AISI  
316L frame / cadre  
en acier inoxydable  
AISI 316L / cornis  
acero inox AISI 316L  
/ Rahmen aus  
Edelstahl AISI 316L



code: ...M



230x88 mm

art.	art.		W	V	Type	Light Bulb Icon	Ra
412L6NM	413L6NM	○	6	240	4000K 660LM	80	
412L6HM	413L6HM	●			3000K 600LM	80	
412M	413M		1x40		E27	Light Bulb Icon	

