

mira 45 LT

LED
powered by
CREE XPG2

simmetrico
symmetric
symétriques
simétrico
symmetrisch

example code:
art. LED anodized
4157 LL2 H inx

art.
4157

design Ufficio Tecnico Landa



corpo alluminio estruso
anodizzato
body in extruded aluminum
aluminium
corps en aluminium extrudé
anodisé
cuerpo en aluminio
extrusionado y anodizado
Körper aus eloxiertem
fließgepresst Aluminium

diffusore policarbonato
trasparente
diffuser transparent
polycarbonate
diffuseur polycarbonate
transparent
difusor policarbonato
transparente
Diffuser Polykarbonat klar

RECESSED
16




...brz





...inx



codeLS2



codeLL2



FOR TECHNICAL DETAILS VISIT
www.landa.it

IP66

art.	LUX 1mt	Beam	art.	LUX 1mt	Beam	W	V	Type	Light Bulb	Ra
4157LS2N	1600	10°	4157LL2N	280	40°	2	24	4000K	190LM	80
4157LS2H	1600		4157LL2H	280		2	d.c.	3000K	190LM	80

ELECTRIFICATION

Transformer available:

cod. 0409BT014 to connect up to **5** pieces – GE LIGHTING IP67 24V d.c. 12W
cod. 0409BT015 to connect up to **10** pieces – GE LIGHTING IP67 24V d.c. 25W

Transformer on request:

cod. 0409BT016 to connect up to **42** pieces – GE LIGHTING IP67 24V d.c. 100W



LED & INSTALLATION

dettagli / details / details
detalles / details:
p.A52 - A53

Energy efficiency classes

A++ ÷ A

mira 45 LT (24V)

Projectors



Recessed



Contemporary



Traditional




RECESSED
17



Thanks to Franssen verlichting - NL



...brz



...inx

Accessories on request:



code 0404M009
Single connection IP68

