

serie/series

mira 65

LED

powered by
Philips Luxeon H50-2
AC direct connection
220/240V
Transformer not required

example code:

art.	LED	anodized
5382	L5	H inx

art.
5382
5383
5384
5385
5386



design Ufficio Tecnico Landa

RECESSED

40

corpo alluminio estruso
anodizzato
body in extruded anodized
aluminium
corps en aluminium extrudé
anodisé
cuerpo en aluminio
extrusionado y anodizado
Körper aus eloxiertem
fließgepresst Aluminium

diffusore policarbonato opale
diffuser opal polycarbonate
diffuseur polycarbonate
opaque
difusor policarbonato ópalo
Diffuser Polykarbonat opal




5382



codeL5H



5383






codeLL5H



5384



codeLL5H



FOR TECHNICAL DETAILS VISIT
www.landa.it

IP67

art	art.	art.	W	V	Type	⚡	Ra	ANODIZED		
5382	L5H	5383	LL5H	5384	LL5H	5	240	3000K 400LM 80	brz	inx

ELECTRIFICATION

LED & INSTALLATION

dettagli / details / details
detalles / details:
p.A52 - A53

Energy efficiency classes

A++ ÷ A

mira 65 (AC/240V)



Projectors



NEW
Recessed



Contemporary



Traditional



ENERGY
SAVING

RECESSED

41



5385





codeLL5H



5386



codeLL5H



brz







inx



....brz



....inx

art.	art.		W	V	Type		Ra
5385	LL5H		5	240	3000K	400LM	80
5386	LL5H		5	240	3000K	400LM	80

Accessories on request:



code 0404M009
Single connection IP68

