

mira 220

LED

powered by
Citizen Electronics® LED
AC direct connection
220/240V
Transformer not required



simmetrico
symmetric
symétriques
simétrico
symmetrisch

°C

temperatura sul vetro
glass temperature
température du verre
temperatura del vidrio
Glastemperatur

example code:
art. LED 60° colour
5511 LL20 H ngg

art.

5511
5521
5531
5541

design Ufficio Tecnico Landa



5511

frontale in alluminio / aluminium frame /
cadre en aluminium / cornis aluminio /
Rahmen aus Aluminium


COLOURS




ngg



all






5521



5541

frontale in acciaio inox
AISI 316L / stainless
steel AISI 316L frame
/ cadre en acier
inoxydable AISI 316L /
cornis acero inox AISI
316L / Rahmen aus
Edelstahl AISI 316L




ML2 H07RN-F


FOR TECHNICAL DETAILS VISIT
www.landa.it

IP67


art.	art.	art.		°C	W	V	Type	LUX 1Mt	Ra
5511LS20N	5521LS20N	5541LS20N	○	20°	29	20	4000K 2385LM	6900	80
5511LS20H	5521LS20H	5541LS20H	○				3000K 2280LM	6600	80
5511LM20N	5521LM20N	5541LM20N	○	40°	29	20	4000K 2385LM	2800	80
5511LM20H	5521LM20H	5541LM20H	○				3000K 2280LM	2700	80
5511LL20N	5521LL20N	5541LL20N	○	60°	29	20	4000K 2385LM	1450	80
5511LL30H	5521LL30H	5541LL30H	○				3000K 2280LM	1400	80
5511LS30N	5521LS30N	5541LS30N	○	20°	35	33	4000K 3515LM	9500	80
5511LS30H	5521LS30H	5541LS30H	○				3000K 3300LM	8900	80
5511LM30N	5521LM30N	5541LM30N	○	40°	35	33	4000K 3515LM	4100	80
5511LM30H	5521LM30H	5541LM30H	○				3000K 3300LM	3800	80
5511LL30N	5521LL30N	5541LL30N	○	60°	35	33	4000K 3515LM	2100	80
5511LL30H	5521LL30H	5541LL30H	○				3000K 3300LM	2000	80



codeLS20



codeLM20



codeLL20

A++ ÷ A

Also available with:

cod. 0201001.19B
vetro opale/opal glass/
verre opaque/vidrio ópalo/Glas opal



cod. 0201001.19A
vetro antiscivolo/non-slip glass/
verre anti dérapant/cristal antiresbaladizo/
rutschhemmendes Glas



mira 220

Projectors


Recessed

Contemporary

Traditional




RECESSED
47




5531

frontale in acciaio inox
AISI 316L / stainless
steel AISI 316L frame
/ cadre en acier
inoxydable AISI 316L /
cornis acero inox AISI
316L / Rahmen aus
Edelstahl AISI 316L



filo pavimento
flush
au niveau du sol
a ras de suelo
Bodeneinbau




art.		°C	W	V	Type	LUX 1Mt	Ra
5531LS20N	○	20°	29	20	4000K 2385LM	6900	80
5531LS20H	○				3000K 2280LM	6600	80
5531LM20N	○	40°	29	20	4000K 2385LM	2800	80
5531LM20H	○				3000K 2280LM	2700	80
5531LL20N	○	60°	29	20	4000K 2385LM	1450	80
5531LL20H	○				3000K 2280LM	1400	80
5531LS30N	○	20°	35	33	4000K 3515LM	9500	80
5531LS30H	○				3000K 3300LM	8900	80
5531LM30N	○	40°	35	33	4000K 3515LM	4100	80
5531LM30H	○				3000K 3300LM	3800	80
5531LL30N	○	60°	35	33	4000K 3515LM	2100	80
5531LL30H	○				3000K 3300LM	2000	80

Accessories on request:

Antivandalism set



00KAV03



0303CA3


per/for/pour/
para/für

code: 5511...

Antivandalism set



00KAV04



0303CA3

per/for/pour/
para/für

code: 5521...

code: 5531...

code: 5541...

